

ex. MA-14 on left side and MA-22 on right ex. MA-14C on left side and MA-22C on right

CTC3-24-01PF-B

CTC3-24-01-B

CTC3-24-06-B

CTC3-24-08-B

CTC3-24-04-EXT-B

CTC3-24-04PF-EXT-B

PRODUCT CONFIGURATOR

Q) What is required width of frame?

A) 24" 30"

Q) What is the required depth of the frame for standard or cable trough roof?

A)	IN B	fotor	dord	roof	in	required -
A)	1)	Star	carci	LOCI	IS	reaumea -

width is 24", depth is	30"	item number is	CTC3-2430-B
	36"	item number is	CTC3-2436-B
	42"	item number is	CTC3-2442-B
or			
width is 30", depth is	30"	item number is	CTC3-3030-B
	36"	item number is	CTC3-3036-B
	42"	item number is	CTC3-3042-B

II) if integrated cable trough roof is required -

available only with width of 30"	36"	item number is	CTC3-3036-CT-B
	42"	item number is	CTC3-3042-CT-B

What type of mounting angles, standard or high-density, are required for 19" EIA? May require 2 sets.

I) if standard mounting angle is required -

if cabinet width is 24", tapped style item number is or caged nut style, item number is	item number is item number is	CTC3-MA-22-B CTC3-MA-22C-B
if cabinet width is 30", tapped style item number is	item number is	CTC3-MA-16-B CTC3-MA-16C-B

II) if high density (extra wide) mounting angle is required -

for width of 30" only,

tapped style with fibre loop capability, item number is	item number is	CTC3-MA-14-FL-B	must be used with CTC3-MA-22-B
or cage nut style with fibre loop capability, item number is	item number is	CTC3-MA-14C-FL-B	must be used with CTC3-MA-22C-B

**Customer to specify which side to install the mounting angles. Accessory for use with CTC3-MA-14-FL-B or CTC3-MA-14C-FL-B

> filler panel to reduce air flow, item number is CTC3-MA-14FL-FP-B item number is

Are fibre loops required for use with CTC3-MA-14-FL-B or CTC3-MA-14C-FL-B?

A)	for loop dimensions of 1.2" wide x 3" deep x 2.3" high	item number is	CT-FL-3-B
	for loop dimensions of 2.5" wide x 5.5" deep x 2.5" high	item number is	CT-FL-5.5-NB-B

What style door is required? Need 2 doors per cabinet.

A)	with 24" frame width,	perfora	ite	d with	fl	us	sh	mount	lock

ou 2 400.0 por oubo					
perforated with flush mount lock	item number is	CTC3-24-01PF-B	Cannot use:	perforated	CTC3-30-01PF-B
lexan window with flush mount lock	item number is	CTC3-24-01-B		lexan	CTC3-30-01-B
solid with flush mount lock	item number is	CTC3-24-06-B		solid	CTC3-30-06-B
louvered with flush mount lock	item number is	CTC3-24-08-B		louvered	CTC3-30-08-B
2" extended lexan window with flush mount lock	item number is	CTC3-24-04-EXT-B		2" extended lexan	CTC3-30-04-EXT-B
2" extended perforated window with flush mount lock	item number is	CTC3-24-04PF-EXT-B		2" extended perforated	CTC3-30-04PF-EXT-B

CTC3-30-01PF-B

cannot use:

with 30" frame width, perforated with flush mount lock

lexan window with flush mount lock CTC3-30-01-B item number is solid with flush mount lock item number is CTC3-30-06-B louvered with flush mount lock item number is CTC3-30-08-B 2" extended lexan window with flush mount lock item number is CTC3-30-04-EXT-B CTC3-30-04PF-EXT-B 2" extended perforated window with flush mount lock item number is

item number is

Speak with Cable Talk Rep for options on locks:

push button

3 point

trac latch

key / dial combo

Revised October 15, 2007 Page 1

perforated

louvered

2" extended lexan

2" extended perforated

lexan

solid

^{**} Doors are installed with left hand swing. Right hand swing available upon request.



PRODUCT CONFIGURATOR

What type of side panel is required? Need 2 side panels per cabinet.

Side panels include key locks.

if frame depth is 36",

if frame depth is 30", solid item number is CTC3-30-11-B Cannot use: perforated item number is CTC3-30-11PF-B

solid item number is CTC3-36-11-B Cannot use: perforated item number is CTC3-36-11PF-B

if frame depth is 42", solid item number is CTC3-42-11-B Cannot use: CTC3-30-11-B

CTC3-30-11PF-B CTC3-36-11-B CTC3-36-11PF-B

CTC3-36-11-B

CTC3-30-11-B

CTC3-30-11PF-B CTC3-42-11-B

CTC3-36-11PF-B CTC3-42-11-B

Q) What type of shelf is required for 19" EIA? Choose between 2-position mounting or 4-position mounting.

I) 4-position mount requires 2 sets of mounting angles

if using CTC3-2430-B frame	for fixed-adjustable shelf, with mounting depth of 21 - 26.75"	item number is	CTCS-FAJ-1822-B	cannot use:	CTCS-FAJ-1827-B CTCS-FAJ-1833-B
if using CTC3-2436-B frame	for fixed-adjustable shelf, with mounting depth of 21 - 26.75" for fixed-adjustable shelf, with mounting depth of 26.5 - 31.5"	item number is	CTCS-FAJ-1822-B CTCS-FAJ-1827-B	cannot use:	CTCS-FAJ-1833-B
if using CTC3-2442-B frame	for fixed-adjustable shelf, with mounting depth of 21 - 26.75" for fixed-adjustable shelf, with mounting depth of 26.5 - 31.5" for fixed-adjustable shelf, with mounting depth of 32.5 - 37.5"	item number is	CTCS-FAJ-1822-B CTCS-FAJ-1827-B CTCS-FAJ-1833-B		
if using CTC3-3030-B frame	for fixed-adjustable shelf, with mounting depth of 21 - 26.75" for fixed-adjustable shelf, with mounting depth of 26.5 - 31.5"	item number is	CTCS-FAJ-1822-B	cannot use:	CTCS-FAJ-1827-B CTCS-FAJ-1833-B
if using CTC3-3036-B frame or CTC3-3036-CT-B	for fixed-adjustable shelf, with mounting depth of 21 - 26.75" for fixed-adjustable shelf, with mounting depth of 26.5 - 31.5" for fixed-adjustable shelf, with mounting depth of 32.5 - 37.5"	item number is	CTCS-FAJ-1822-B CTCS-FAJ-1827-B	cannot use:	CTCS-FAJ-1833-B
if using CTC3-3042-B frame or CTC3-3042-CT-B	for fixed-adjustable shelf, with mounting depth of 21 - 26.75" for fixed-adjustable shelf, with mounting depth of 26.5 - 31.5" for fixed-adjustable shelf, with mounting depth of 32.5 - 37.5"	item number is	CTCS-FAJ-1822-B CTCS-FAJ-1827-B CTCS-FAJ-1833-B		
for any size cabinet frame	for retractable shelf with platform depth of 22" for retractable shelf with platform depth of 27"	item number is	CTCS-R-1922-B CTCS-R-1927-B		
II) 2-position mount requires 1 set for any size cabinet frame	s of mounting angles for solid platform with 11" depth, 1U high	item number is	CTRS-F-1811-1U-B		
	for solid platform with 12" depth, 2U high	item number is	CTRS-F-1812-B		
	for vented platform with 17" depth, 2U high	item number is	CTRS-F-1817-2U-B		
	for vented platform with 17" depth, 3U high	item number is	CTRS-F-1817-B		
	for vented platform with 21" depth, 3U high	item number is	CTRS-F-1821-B		
	for retractable 3-in-1 shelf, vented platform, 3U high	item number is	CTRS-R3-19-B		

Revised October 15, 2007 Page 2



PRODUCT CONFIGURATOR

Q) What style of vertical cable management is required?

I) To be used in 24" wide frames, 83" H

for Flat Backbone Cable Mangement which is 4" wide item number is CTC3-CMS-30-B for Ladder Backbone Cable Management which is 4.25" wide item number is CTC3-CMS-33-B for Ladder Backbone Cable Management which is 12" wide item number is CTC3-CMS-34-B

II) To be used in 30" wide frames, 83" H

for Channel Cable Management, narrow style is 5" wide item number is CTC3-CMS-11-B for Channel Cable Management, deep style is 9" wide item number is CTC3-CMS-12-B for Flat Backbone Cable Management which is 4" wide item number is CTC3-CMS-30-B for Ladder Backbone Cable Management which is 4.25" wide item number is CTC3-CMS-33-B for Ladder Backbone Cable Management which is 12" wide item number is CTC3-CMS-34-B

III) To be used in 30" wide cabinet with CTC3-MA-14-B or CTC3-MA-14C-B $\,$

for High Density Channel Cable Management which is 6" wide item number is CTC3-CMS-13-B

Accessories for use with CTC3-CMS-13-B

1. strain relief waterfalls item number is CTC3-CMS-13-SR-B

What style of horizontal cable management is required?

The following styles will fit on any size cabinet frame with 19" EAI standard mounting.

for Standard Horizontal Cable, 3" deep and 1 U-space	item number is	CTH-CMS-1M-B
for Standard Horizontal Cable, 3" deep and 2 U-space	item number is	CTH-CMS-2M-B
for Standard Horizontal Cable, 3" deep and 3 U-space	item number is	CTH-CMS-3M-B
for Standard Horizontal Cable, 3" deep and 4 U-space	item number is	CTH-CMS-4M-B
for Fingered Horizontal Cable, 3" deep and 1 U-space	item number is	CTH-CMS-1FM-B
for Fingered Horizontal Cable, 3" deep and 2 U-space	item number is	CTH-CMS-2FM-B
for Fingered Horizontal Cable, 3" deep and 3 U-space	item number is	CTH-CMS-3FM-B
for D-Ring Horizontal Cable, 3" deep and 1 U-space	item number is	CTH-CMS-1D5-B
for D-Ring Horizontal Cable, 3" deep and 2 U-space	item number is	CTH-CMS-2D5-B

Q) What type of vertical power bar is required?

A) The following power bars will fit on any size cabinet frame.

for 8 outlets, 15A, 7' cord, item number is CTPBV-0850-B for 10 outlets, 15A, 7' cord item number is CTPBV-1029-B for 12 outlets, 15A, 7' cord item number is CTPBV-1277-B

options: 20A, switch disabled, twist lock, 15' cord, shielded cord, metered reading

Q) What type of horizontal power bar is required? Choose between power bar with MOV or power distribution strip with no MOVs.

A) The following power bars will fit on any size cabinet frame with 19" EAI standard mounting.

1) power bar with noise filter and surge protection (MOVs), 6 outlets, 15A, 7' cord, 1 U-space item number is CTPBH-0619-B options: 20A, switch disabled, twist lock, 15' cord, shielded cord, metered reading

II) power distribution strip with no noise filter and surge protection (MOVs), 6 outlets, 15A, 6' cord, straight blade plug item number is CTPBH-0619U-B

Q) How many fans are required?

A) The following fan assemblies will fit on any size cabinet frame, 83" H.

for 1 fan item number is CTC-FA-1 for 2 fan item number is CTC-FA-2 for 4 fan item number is CTC-FA-4

Q) Are casters required? Caster kit includes mounting plate, 2 fixed casters & 2 swivel casters.

A) for 24" width cabinet, item number is CTC-K-48-24CAB for 30" width cabinet, item number is CTC-K-48-30CAB

Revised October 15, 2007 Page 3